



ZZ 1560

Global[®] ZZ 1560 Series - High speed zig-zag machines

TECHNICAL SPECIFICATIONS

Machine speed*
up to 5000 spm

Stitch type
304

Number of needles
1

Feed type
drop feed

Zig-zag width
0-10 mm max.

Stitch length
max. 5 mm

Hook type
1565 standard hook
1566 / 1568 large hook

Needle type
134R

Presser foot lift
6 mm

Optional extra's ZZ 1560:

- **presser foot lift**
- **back tack**

(all pneumatic or electric)

ZZ 1560 - High speed zig-zag machines, semi automatic lubrication, built-in bobbinwinder. Sliding excenter reverse feed, pendant link feed mechanism.

ZZ 1560 AUT - Same as ZZ 1560, but equipped with automatic thread trimmer, back tack and presser foot lifter. (all electric)

MAQUINAS DE ZIG ZAG

ZZ 1560 - Máquinas de zig zag de alta velocidad, lubricación semi automática, devanador de canilla acoplado. Deslizamiento excéntrico del inversor de puntada y mecanismo de transmisión del arrastre suspendido.

ZZ 1560 AUT - La misma que ZZ 1560, pero equipada con corta-hilos automático, alza-prensateles y remate automático. (eléctrico)

ZICK-ZACK SCHNELLNÄHER

ZZ 1560 - Hochleistungs Zick-Zack Schnellnäher mit halbautomatischer Schmierung und eingebautem Spulapparat. Umschaltung auf Rückwärtsstich durch Gelenk und Gleitexcenter.

ZZ 1560 AUT - Baugleich mit ZZ 1560, jedoch ausgestattet mit automatischem Fadenabschneider, Fußlüftung und Verriegelung. (elektrisch)

MACHINE ZIG-ZAG


ZZ 1560 - Machine zig-zag à grande vitesse, lubrification semi automatique, bobinoir incorporé. Marche arrière par excentrique, mécanisme de griffe par bielles suspendues.

ZZ 1560 AUT - Identique à la ZZ 1560, mais équipée avec coupe-fil, relevage de pied et arrêt automatiques (électromagnétique)


Global ZZ 1560 series

The ZZ 1560 series are semi-lubricated, fast running, zig-zag machines.


ZZ 1560 series are usable on a wide variety of materials. These machines are also available with an electric underbed thread trimmer, back tack and presser foot lifter (electric).



Global ZZ 1566



Global ZZ 1565



Global ZZ 1565

Specifications

model		number of needles	max. stitch length mm	max. stitch width mm	presser foot lift mm	space to right of needle mm	needle system	max. sewing speed spm*	thread trimming device	hook
ZZ 1565	High speed 6 mm flatbed zig zag sewing machine	1	5	6	6	270	134R	5500	—	standard
ZZ 1565 AUT	Same as ZZ 1565 - but with thread trimmer, back tack and presser foot lifter (electric)	1	5	6	6	270	134R	5000	●	standard
ZZ 1566	High speed 10 mm flatbed zig-zag sewing machine	1	5	10	6	270	134R	4400	—	large
ZZ 1566 AUT	Same as ZZ 1566 - but with thread trimmer, back tack and presser foot lifter (electric)	1	5	10	6	270	134R	4400	●	large
ZZ 1568	High speed 10 mm flatbed zig-zag sewing machine for medium heavy fabric	1	5	10	6	270	134R	3400	—	large
ZZ 1568 AUT	Same as ZZ 1568 - but with thread trimmer, back tack and presser foot lifter (electric)	1	5	10	6	270	134R	3400	●	large

★ Max. sewing speed (in spm.) depends on type of operation and/or materials to be sewn.

The GLOBAL® Selection is brought to you by:

GLOBAL® is a trademark of the Global International Corporation, the people that carefully organize the supply of spareparts before they launch each product.

When ordering parts please specify:

- 1 machine model
- 2 part numbers